TFAWS Passive Thermal Paper Session





GRC · 2014

LUROVA - From Render Engine to Thermal Model

Ron Creel
Apollo Lunar Roving Vehicle Team Member



Apollo Rover on the Moon

Thermal & Fluids Analysis Workshop TFAWS 2014 August 4 - 8, 2014 NASA Glenn Research Center Cleveland, OH

LUROVA Introduced at TFAWS-2006




 Full Interactive Mission Support Thermal Model Needed for LUROVA Book and STEM Challenge Simulation for Students








LUROVA Book






LUROVA Mission Support Thermal Models






Mobility Subsystem TVAC Testing



LOHARP Calculated View Factors and "Wireframe" Verification Plots

- 177 Node "Full" Model Correlated with TVAC Testing
- Separate Forward,
 Center, and Aft Section
 Models Required Due
 to LOHARP 140
 Surface Node Limit






Qualification and Flight Units TVAC



View Factor Verification using Full Scale LM Model at U.S. Space and Rocket Center

Render Engine Provides High Quality Surface Data

- Original "Full" Rover Thermal Model Nodes and Linear Conductors
 Located, But No Surface Model for Radiation Conductors and Heat Rates
- Candidate "Lightwave" Rendered Polygons Used for Rover Poster




Too Many Polygon Surfaces for TRASYS 4000 Node Limit

489,731 Vertices



Polygon Reduction/Conversion (R/C) Process Developed






Polygon Reduction Steps & Products

TFAWS 2014 – August 4 -8, 2014




 Render Engine Polygons Selected and Reduced for Forward Chassis Thermal Model



1 3D Web Browser Used to Select Forward Chassis Model Nodes

Polygon Cruncher Used to Reduce Number of Triangular Polygons



CENTER CHASSIS



Triangular Polygons Converted to TRASYS Trapezoids




```
Input
   Msers\Ron d:
  \ROUER>cd lurova
  NOVER\lurova>cd thermal model
                                                                                                           ATA_REPORT - The input file contains:
  ROVER\lurova\thermal model>cd cruncher
                                                                                                             Text lines
Duplicate points
ello: This is IVRead,
a program which can convert some files from
some 3D graphics format to some others:
                                                                                                              Jertices per face, maximum
                   3D Studio Max ASCII export;
Movie.BYU surface geometry;
Suft Inage hierarch;
Suft Inage hierarch;
Suft Inage hierarch;
VaveFront Revanced Visualizer;
Geomiew OFF file;
OGG, File (input only);
Persistence of Vision (output only);
Persistence of Vision (output only);
RestI Stereolithography;
ASCII Stereolithography;
                                                                                                              Materials
                                                                                                            BJ_WRITE - Wrote 25667 text lines to 701_out.obj
                                                                                                            UREAD:
Normal end of execution.
                                                                                                              July 2014 6:31:36.042 PM
                                                                                                            D:\ROUER\lurova\thernal_model\cruncher)
                       SCII Stereolithography;
ECPLOT (output only);
Greg Hood triangles, ASCIII;
Greg Hood triangles, ASCIII;
dathenatica ThreeScript (output only);
dathenatica ThreeScript (output only);
                      XGL (output only) (DEVELOPMENT)
XYZ (points and lines);
```

```
Output
```

```
701_out.obj - Notepad
File Edit Format View Help
# 701_out.obj created by IVREAD.
# Original data in 701.obj.
g Group001
v 0.185530 -0.639192 -0.355888 1.00000
v 0.187721 -0.649190 -0.357875 1.00000
v 0.185650 -0.647000 -0.363044 1.00000
v 0.183367 -0.638798 -0.362232 1.00000
    /5 6//6 5//7 2//8
     /9 8//10 7//11 5//12
     /13 2//14 10//15 9//16
        5//18 11//19 10//20
7//22 12//23 11//24
    /25 10//26 14//27 13//28
  10//29 11//30 15//31 14//32
  11//33 12//34 16//35 15//36
f 15//37 16//38 17//39
```

IVREAD Converts
 Reduced Polygon "Faces"
 and "Vertices" to ".obj"
 Readable Ascii Format




Forward Chassis Surface Model

CONVERT Provides TRASYS

Trapezoids for Calculating
Radiation Conductors, and

Correspondence to Combine
Polygons for Surface Nodes
Heat Rates, and Areas,

Allows Mirroring for Symmetrical Mobility Subsystems and Coordinate Rotations for Variable Solar Orientation



```
HEADER OPTIONS DATA
TITLE LUROVA
      MODEL = LUROVA
      RSO
HEADER SURFACE
       SURFN
                   = 601001
             -0.46338487 , -3.09466863 , -0.89315426
            -1.28817642 , -2.37285924 , -0.89315426
            -1.28817642 , -3.09466863 , -0.89315426
       P4 = -0.46338487 , -3.09466863 , -0.89315426
       NNY = 1
                   = 601002
       SURFN
       TYPE
                   = TRAP
       ACTIVE
                   = 0.90, 0.90
             -0.46338487 , -2.37285924 , -0.89315426
            -1.28817642 , -2.37285924 , -0.89315426
             -0.46338487 , -3.09466863 , -0.89315426
       P4 = -0.46338487 , -2.37285924 , -0.89315426
       NNY = 1
                   = 602001
       SURFN
                   = TRAP
       ACTIVE
              0.75579894 , -2.38128114 , -0.94096255
             1.61763108 , -3.08834314 , -0.94096255
             1.61763108 , -2.38128114 , -0.94096255
       P3 =
              0.75579894 , -2.38128114 , -0.94096255
```


```
HEADER CORRESPONDENCE DATA
      LUROVA
       601001,601002
       602 =
       602001,602002
       603 =
       603001,603002
       606001,606002,606003,606004
       608001,608002,608003,608004,608005,608006,608007,
       608008,608009,608010
       609 =
       609001,609002,609003,609004,609005,609006,609007,
       609008,609009,609010,609011,609012,609013,609014,
       609015, 609016, 609017, 609018, 609019, 609020, 609021,
       609022,609023,609024,609025,609026,609027,609028,
       609029,609030,609031,609032,609033,609034,609035,
       609036,609037,609038,609039,609040,609041,609042
       610 =
       610001, 610002, 610003, 610004, 610005, 610006, 610007,
       610008, 610009, 610010, 610011, 610012, 610013, 610014,
       610015, 610016, 610017, 610018, 610019, 610020, 610021,
       610022,610023,610024,610025,610026,610027,610028,
       610029,610030,610031,610032,610033,610034,610035
```



Reduction and Conversion Process Verification




 Surface Plot Programs Provide Visual Verification for R/C Processed Forward Chassis Surface Nodes



R/C Process Heat Rates Comparison



TRASYS Calculated Forward Chassis Node Heat Rates Verified





R/C Processed Model Temperature Comparison



- Next Step is to Compile SINDA Model to Compare with 19 Node Mission Model
 Recently Used for NASA Nightrover Centennial Challenge for Energy Storage
- Apollo 17 Last EVA and After +249 deg. F for Latitude = 20.16 N 250 200 Daytime 150 Insulated with Survival Power Required for 60 deg. F Daytime Isolation and 100 37.4 watts for 53.6 kg Batteries Insulated with **Covers Closed** 247 watt-hr/kg for 354 hours nighttime deg. Isolation and **Thermal Model Components** FORWARD CHASSIS STRUCTURE NODES \$FORWARD RAIL, RIGHT HALF \$FORWARD RAIL, LEFT HALF 101, 100.0, 0.2514 Covers Open DRIVE CONTROL ELECTRONICS AND THERMAL CONTROL UNIT 102, 100.0, 0.2514 103, 100.0, 1.7711 104, 100.0, 1.7711 105, 100.0, 0.1924 106, 100.0, 0.1924 107, 100.0, 0.0825 108, 100.0, 0.0825 109, 100.0, 0.0565 110, 100.0, 0.0989 **Temperature** SBATTERY SUPPORT CHANNEL SBATTERY SUPPORT CHANNEL - LEFT HALF Covers \$RIGHT SUPPORT CHANNEL \$LEFT SUPPORT CHANNEL \$STEERING SUPPORT CHANNEL close SLOWER SKIN PANEL SUPPER SKIN PANEL SAFT CHANNEL, RIGHT HALF SAFT CHANNEL, LEFT HALF 111. 100.0. 0.0989 121, 100.0, 1.0048 122, 100.0, 1.0048 123, 100.0, 0.5880 124, 100.0, 0.3687 125, 100.0, 0.5880 SRIGHT SIDE RAIL, FORWARD HALF SCENTER RAIL, FORWARD HALF SLEFT SIDE RAIL, FORWARD HALF 126, 100.0, 0.2414 \$FLOOR PANEL, RIGHT FORWARD QUARTER 126, 100.0, 0.2414 127, 100.0, 0.2414 128, 100.0, 0.6278 129, 100.0, 0.3687 130, 100.0, 0.6278 131, 100.0, 0.2414 132, 100.0, 0.2414 133, 100.0, 0.7085 134, 100.0, 0.7085 **Moon Temperature** SFLOOR PANEL, LEFT FORWARD QUARTER SRIGHT SIDE RAIL, AFT HALF SCENTER RAIL, AFT HALF SLEFT SIDE RAIL, AFT HALF INSULATION BLANKE 15 LAYERS OF IGNAL PROCESSING UNIT -150 SFLOOR PANEL, RIGHT AFT QUARTER SFLOOR PANEL, LEFT AFT QUARTER SAFT RAIL, RIGHT HALF SAFT RAIL, LEFT HALF ALUMINIZED MYLAR (SPU) (DUST COVER NOT SHOWN) AND NYLON NETTING BATTERY NO, 2 WITH BETA CLOTH DUST COVER, BATTERY NO. 2 EXTERNAL SURFACES AFT CHASSIS STRUCTURE NODES SFORWARD CHANNEL, RIGHT HALF 141, 100.0, 0.0896 SRIGHT SIDE RAIL SRIGHT SUPPORT CHANNEL SLEFT SUPPORT CHANNEL -200 Nighttime No Survival -250 Sunset Sunrise Power -281 deg. F for Latitude = 20.16 N --


1000






- Use Successful R/C Process to Add Rover Center and Aft Model Sections
- Complete Interactive SINDA Thermal Model for Book and DVD Simulation
 - Driving with Astronauts, and Parked with Covers Closed/Open and LM
- Use R/C Process for LM/CSM Transportation Phase Model

Passive
Thermal Control
(PTC)
"Barbeque"
Rotation
(3 revs/hr)






PTC - Solar Heating Simulation



Expand "Additive Manufacturing" 3D Model for Student Awards

NASA/MSFC Sponsoring 3D Printer for ISS Experiments





Printed Rover Forward
Chassis Model
Created Using MSFC
3D Printer

 Continue STEM Student Lectures and Support to <u>Human Exploration</u> <u>Rover Challenge</u> (formerly Moonbuggy Races)